

## **Product Handling Information Sheet**

## Foamlite® G 752 + UV-stabilized black

Name/Address   Röchling Industrial SE & Co. KG   Röchlingstr.   • 49733 Haren (Ems)/Germany (DE) • Tel. • 49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren	1. Company					
Product/Article Abbreviated terms PE-HD / PE 300 Material Characterisation Main Components  • polyethylene • stabiliser • additives  Components Subject to labelling Classification according to REACh Notes  -  3. Product characteristics Form/State • firm Color Odour • nearly odourless  Density  0,75  Melting range Glass transition temperature Thermal decomposition  PE-HD / PE 300  Semi-crystalline plastic  • polyethylene • stabiliser • additives  Article  Article  Product characteristics  • firm  • firm  O,75  Melting range  133 135  Glass transition temperature  - Thermal decomposition  > 390°C	Name/Address	Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0				
Product/Article Technical semi-finished product or machined part  Abbreviated terms PE-HD / PE 300  Material Characterisation Semi crystalline plastic  Main Components						
Abbreviated terms PE-HD / PE 300  Material Characterisation Semi crystalline plastic  Main Components • polyethylene • stabiliser • additives  Components Subject to labelling none  Classification according to REACh Article  Notes -  3. Product characteristics  Form/State • firm  Color black  Odour • nearly odourless  Density 0,75  Melting range 133 135  Glass transition temperature - Thermal decomposition >390°C	2. Product details					
Material Characterisation       Semi crystalline plastic         Main Components       • polyethylene         • stabiliser       • additives         Components Subject to labelling       none         Classification according to REACh       Article         Notes       -         3. Product characteristics         Form/State       • firm         Color       black         Odour       • nearly odourless         Density       0,75         Melting range       133 135         Glass transition temperature       -         Thermal decomposition       >390°C	Product/Article	Technical semi-finished product or machined part				
Main Components  • polyethylene • stabiliser • additives  Components Subject to labelling none Classification according to REACh Notes  -  3. Product characteristics Form/State • firm Color black Odour • nearly odourless Density 0,75 Melting range 133 135 Glass transition temperature Thermal decomposition  • polyethylene • stabiliser • additives  Article  Article  Article  -  133 135    Solution	Abbreviated terms	PE-HD / PE 300				
• stabiliser • additives  Components Subject to labelling none  Classification according to REACh Article  Notes  -  3. Product characteristics  Form/State • firm  Color black  Odour • nearly odourless  Density 0,75  Melting range 133 135  Glass transition temperature Thermal decomposition  > sapo°C	Material Characterisation	Semi crystalline plastic				
Classification according to REACh Notes  -  3. Product characteristics  Form/State  • firm  Color  black  Odour  • nearly odourless  Density  Melting range  Glass transition temperature  Thermal decomposition  Article  Article  Article  Article  Article  Article  • IIII  Article  • IIII  FIRM  Article  FIRM  Article	Main Components	• stabiliser				
3. Product characteristics  Form/State • firm  Color black  Odour • nearly odourless  Density 0,75  Melting range 133 135  Glass transition temperature - Thermal decomposition >390°C	Components Subject to labelling	none				
3. Product characteristics  Form/State • firm  Color black  Odour • nearly odourless  Density 0,75  Melting range 133 135  Glass transition temperature -  Thermal decomposition >390°C	Classification according to REACh	Article				
Form/State         • firm           Color         black           Odour         • nearly odourless           Density         0,75           Melting range         133 135           Glass transition temperature         -           Thermal decomposition         >390°C	Notes					
Color black Odour • nearly odourless  Density 0,75  Melting range 133 135  Glass transition temperature - Thermal decomposition >390°C	3. Product characteristics					
Odour  • nearly odourless  Density  0,75  Melting range 133 135  Glass transition temperature Thermal decomposition  • nearly odourless  0,75  135  137  138  1390°C	Form/State	• firm				
Density 0,75  Melting range 133 135  Glass transition temperature - Thermal decomposition >390°C	Color	black				
Melting range 133 135  Glass transition temperature –  Thermal decomposition >390°C	Odour	nearly odourless				
Glass transition temperature – Thermal decomposition >390°C	Density	0,75				
Thermal decomposition >390°C	Melting range	133 135				
	Glass transition temperature	-				
Flash point ~340°C	Thermal decomposition	>390°C				
11d311 point ~540 C	Flash point	≈340°C				





Ignition temperature	>350°C					
Notes	<del>-</del>					
4. Danger warnings						
Special Risks For Mankind And The Environment	none					
Notes	<u>-</u>					
5. Handling and Storage						
Handling	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>					
Storage	<ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> </ul>					
Safety measures						
Shelf Life	-					
Notes	-					
6. Transport						
Transport	<ul> <li>Non dangerous goods according to the transport regulations.</li> <li>Secure against slipping.</li> </ul>					
Finished Product Packing	_					



## **Industrial**



• water
• foam
• CO <sub>2</sub>
dry powder extinguishing agents
• CO <sub>2</sub>
Complete protection equipment for fire-brigade.
Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	<ul> <li>12 01 05 plastics shavings and turnings</li> <li>20 01 39 plastics</li> </ul>
Notes	-

9. Marking and Guidelines					
Marking in accordance with Guideline	EEC	no labelling r	equired		
Notes		-			

10. Information about REACh						
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.					

## 11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



