

# **Product Handling Information Sheet**

## Polystone® D nuclear black

1. Company	
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PE-HD / PE 500
Material Characterisation	Semi crystalline plastic
Main Components	<ul> <li>polyethylene</li> <li>possibly olefin-copolymerisate</li> <li>stabiliser</li> <li>additives</li> <li>boron trioxide</li> </ul>
Components Subject to labelling	Boron trioxide (CAS-No. 1303-86-2)
Classification according to REACh	Article
Notes	-

3. Product characteristics	
Form/State	• firm
Color	black
Odour	nearly odourless
Density	>1,05
Melting range	130 135
Glass transition temperature	-





3. Product characteristics	
>390°C	
-	
> 350°C	
-	

4. Danger warnings					
Special Risks For Mankind A Environment	The none				
Notes	Boron trioxide could react with water to boric acid.				
5. Handling and Storage					
Handling	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>				
Storage	<ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> </ul>				
Safety measures					
Shelf Life					
Notes	Do not drink, eat or smoke during the machining process.				

6. Transport	
Transport	<ul><li>Non dangerous goods according to the transport regulations.</li><li>Secure against slipping.</li></ul>
Finished Product Packing	-
Notes	-

#### 7. Fire – fighting measures



### **Industrial**



Suitable extinguishing agents	• foam			
	• CO <sub>2</sub>			
	<ul> <li>dry powder extinguishing agents</li> </ul>			
Potential combustion products	• CO			
	• CO <sub>2</sub>			
	• boron oxide			
Necessary protection equipment	Complete protection equipment for fire-brigade.			
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.			

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	<ul> <li>17 02 04 glass / plastic and wood containing or contaminated with hazardous substances</li> </ul>
Notes	-

9. Marking and Guidelines					
Marking in accordance with Guideline	EEC	no labelling r	equired		
Notes		-			

10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.

#### 11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



