

Product Handling Information Sheet

> 390°C

Polystone[®] M ESD 90 black

1. Company						
Name/Address		Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren				
2. Product details						
Product/Article		Technical semi-finished product or machined part				
Abbreviated terms		PE-UHMW / PE 1000				
Material Characterisation		Semi crystalline plastic				
Main Components		polyethylenepossibly olefin-copolymerisatestabiliseradditives				
Components Subject to lab	elling	none				
Classification according to	REACh	Article				
Notes						
3. Product characteristics						
Form/State		• firm				
Color		black				
Odour		nearly odourless				
Density		>0,94				
Melting range		130 135				
Glass transition temperatur	e	-				
	-					



Thermal decomposition



Flash point	≈ 340°C
Ignition temperature	> 350°C
Notes	

Special Risks For Mankind And The Environment	none					
Notes	-					
5. Handling and Storage						
Handling	Product can be worked with conventional machines and tools.					

5. Handling and Storage	
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.
Storage	 horizontally dry protected against frost protected against climatic influences
Safety measures	Protect against overheating.Carry protective mask and eye protector with dusty condition.
Shelf Life	-
Notes	

6. Transport						
Transport	 Non dangerous goods according to the transport regulations. Secure against slipping. 					
Finished Product Packing	-					
Notes	By the processing under high temperatures gases can outcome, this gases can cause irritation the eyes and respiratory tract.					

7. Fire – fighting measures



Industrial



Suitable extinguishing agents	• water
	• foam
	• CO ₂
	 dry powder extinguishing agents
Potential combustion products	• CO
	• CO ₂
Necessary protection equipment	Complete protection equipment for fire-brigade.
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	12 01 05 plastics shavings and turnings20 01 39 plastics
Notes	-

9. Marking and Guidelines					
Marking in accordance with Guideline	EEC	no labelling r	equired		
Notes		-			

10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.

11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



