

Product Handling Information Sheet

Sustamid® 6 GF 30 black

·	(DE) T 40.0(0) (O7.0					
Product/Article Engineering semi-finished product Abbreviated terms PA 6 Material Characterisation Thermoplastic Main Components • polyamide 6	Röchling Industrial Lahnstein SE & Co. KG Sustaplast-Str. 1 • 56112 Lahnstein/Germany (DE) • Tel. +49 2621 693-0 info.lahnstein@roechling.com • www.roechling.com/industrial/lahnstein					
Product/Article Engineering semi-finished product Abbreviated terms PA 6 Material Characterisation Thermoplastic Main Components • polyamide 6						
Abbreviated terms PA 6 Material Characterisation Thermoplastic Main Components • polyamide 6						
Material Characterisation Main Components • polyamide 6						
Main Components • polyamide 6						
 evtl. colour pigments 	• contains glass fibre					
Components Subject to labelling none	none					
Classification according to REACh Article	Article					
Notes -						
3. Product characteristics						
Form/State • solid						
Color black	black					
Odour • odourless	• odourless					
Density 1,35	1,35					
Melting range 220	220					
Glass transition temperature –						
Thermal decomposition >300 °C	>300 °C					
Flash point -						





3. Product characteristics	
Ignition temperature	>400 °C
Notes	-
4. Danger warnings	
Special Risks For Mankind And Environment	Гће попе
Notes	<u>-</u>
5. Handling and Storage	
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.
Storage	horizontallydryprotected against climatic influences
Safety measures	
Shelf Life	-
Notes	-
6. Transport	
Transport	 Not classified as hazardous good under transport regulations.
Finished Product Packing	-
Notes	-
7. Fire – fighting measures	
Suitable extinguishing agents	 water foam dry extinguishing media CO₂





Potential combustion products	• carbon monoxide
	nitrogen oxide
	traces of hydrogen cyanide
Necessary protection equipment	• Fire fighters and others exposed to combustion products should wear full
	protective clothing and self-contained breathing apparatus.
Notes	Molten product should be cooled by water spray. Dispose fire debris and contaminated extinguishing water in accordance with local regulations.

8. Removal					
Recyclability	Check possibility of recycling.				
EC Waste Catalog	According the European waste catalogue (EAK) the product is not classified as hazardous.				
Waste Removal	Waste disposal by landfill or incineration in compliance with state and local regulations.				
EC Waste Code	12 01 05 plastics shavings and turnings07 02 13 waste plastic				
Notes	-				

9. Marking and Guidelines						
Marking in accordance with Guideline	EEC	not subject to lab	pelling			
Notes		-				

10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore not required to issue safety sheets.

11. Other Information







Other Information

All above mentioned information are based on our current state of knowledge and ensure no warranty of quality. Existing laws and regulations have to be observed by the recepient of our products on his own authority.



