

Product Handling Information Sheet Trovidur[®] ESA-S

1. Company			
Name/Address	Röchling Industrial SE & Co. KG - Troisdorf Mülheimer Str. 26 - Geb. 115 • 53840 Troisdorf/DE • Tel. +49 2241 4820-0 info@roechling-plastics.com • www.roechling.com/industrial/troisdorf		
2. Product details			
Product/Article	Technical semi-finished product or machined part		
Abbreviated terms	PVC-U		
Material Characterisation	Amorphous plastic		
Main Components	 polyvinyl chloride stabiliser additive 		
Components Subject to labelling	-		
Classification according to REACh	Article		
Notes	-		

3. Product characteristics		
Form/State	• firm	
Color	-	
Odour	nearly odourless	
Density	1,41	
Melting range	-	
Glass transition temperature	-	
Thermal decomposition	>180°C	
Flash point		



Röchling

3. Product characteristics		
Ignition temperature	>450°C	
Notes	-	

Special Risks For Mankind And Tl Environment	e none
Notes	-
5. Handling and Storage	
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions. While the processing sufficient for enough airing or by smoke attack provide for a extraction.
Storage	horizontallydry

	 protecte 	ed against f ed against c tore with flo	limatio				
Safety measures							
Shelf Life	-						
Notes		tion the eye	s and r	espiratory [.]		utcome, these gases ca ective film must be	n

6. Transport	
Transport	 Non dangerous goods according to the transport regulations. Secure against slipping.
Finished Product Packing	-
Notes	-



Röchling

Industrial

7. Fire – fighting measures			
Suitable extinguishing agents	• water mist		
	• foam		
	 dry powder extinguishing agents 		
Potential combustion products	carbon monoxide		
	• CO ₂		
	hydrochloric acid		
	hydrocarbon		
Necessary protection equipment	Complete protection equipment for fire-brigade.		
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.		

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	 12 01 05 plastics shavings and turnings 20 01 39 plastics
Notes	This material can to 100 % be recycled.

9. Marking and Guidelines		
Marking in accordance with EEC Guideline	no labelling required	
Notes	-	


10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore not required to issue safety sheets.



Print: 26/12/2024 • Release: 10/10/2024 • Version: 3.0 PIM-Version: 56 • PIM-ID: 709782 • PIM-Code: 56-14

Röchling

11. Other Information Other Information The information in this document are based on our today's knowledge and represent no affirmation of characteristics.Existing laws and regulations are to be observed by the user of our product within his own responsibility.





Print: 26/12/2024 • Release: 10/10/2024 • Version: 3.0 PIM-Version: 56 • PIM-ID: 709782 • PIM-Code: 56-14