




Metric Standoff Insulators




SERIES 2165
PANEL & SWITCHBOARD INSULATORS




1603 SERIES
600 VOLT HIGH STRENGTH
STANDOFF INSULATOR



SERIES 2017
CENTER-POST INSULATORS



SERIES 1463
APPARATUS
STANDOFF INSULATORS



SERIES 1874

Part No.	Height	Thread Size	Voltage	Short Time	Tensile Strength (Lbs.)	Cantilever Strength (Lbs.)		Torque	Arc	UL Subject 94 Flame Resistance	Height	Creep Distance (In.)	Insert	Track
2165-5A	25MM	M6	600	18.6	1,000	400	8,000	12	180	94 V-0	±.015	1½ + Insulator Height	Brass	600
2165-3A	25MM	M6	600	18.6	1,000	400	8,000	12	180	94 V-0	±.015	1½ + Insulator Height	Alum.	600
2165-5B	32MM	M6	600	—	1,000	400	8,000	12	180	94 V-0	±.015	1½ + Insulator Height	Brass	600
2165-3B	32MM	M6	600	—	1,000	400	8,000	12	180	94 V-0	±.015	1½ + Insulator Height	Alum.	600
1603-408	35MM	M8	600	10.0	2,000	1,500	20,000	25	180	94 V-0	±.015	1½ + Insulator Height	Brass	600
1603-410	35MM	M10	600	10.0	5,000	1,800	20,000	30	180	94 V-0	±.015	1½ + Insulator Height	Brass	600
2017-1A	38MM	M6	1500	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-2A	38MM	M8	1500	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-3A	38MM	M10	1500	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-2B	45MM	M8	2000	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-3B	45MM	M10	2000	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-2C	50MM	M8	2300	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-3C	50MM	M10	2300	43.1	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-4C	50MM	M12	2300	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-3D	56MM	M10	2700	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
2017-4D	56MM	M12	2700	—	2,000	1,750	20,000	40	180	94 V-0	±.015	¼ + Insulator Height	Brass	600
1463-1A	53MM	M10	2500	49.3	3,000	3,500	60,000	50	180	94 V-0	±.015	3½ + Insulator Height	Brass	600
1463-1B	53MM	M12	2500	27.9	3,000	3,500	60,000	50	180	94 V-0	±.015	3½ + Insulator Height	Brass	600
1463-1C	53MM	M16	2500	21.0	3,000	3,500	60,000	50	180	94 V-0	±.015	3½ + Insulator Height	Brass	600
1874-1A	63MM	M10	3200	51.4	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-2A	63MM	M12	3200	51.4	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-3F	66MM	M16	3400	33.4	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-1B	70MM	M10	3600	33.4	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-2B	70MM	M12	3600	33.4	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-1C	75MM	M10	4100	—	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-2C	75MM	M12	4100	—	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-1D	81MM	M10	4500	43.1	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-2D	81MM	M12	4500	43.1	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-1E	87MM	M10	5000	55.2	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-2E	87MM	M12	5000	55.2	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600
1874-3E	87MM	M16	5000	55.2	2,500	3,000	60,000	50	180	94 V-0	±.015	5½ + Insulator Height	Brass	600

Mar-Bal, Incorporated

5400 Reserve Way • Dublin, VA 24084 USA • Tel: 540-674-5320 • Fax: 540-674-5328 • www.mar-bal.com

All of the information, suggestions, and recommendations pertaining to the properties and uses of the Glastic products described herein are based upon tests and data believed to be accurate; however, the final determination regarding the suitability of any material described herein for the use contemplated, the manner of such use, and whether the use infringes any patents is the sole responsibility of the user. THERE IS NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Under no circumstances shall we be liable for incidental or consequential loss or damage.

Glastic® is a registered trademark of Röchling Glastic Composites. UL® is a registered trademark of Underwriters Laboratories, Inc.

©2012 Mar-Bal, Incorporated. All Rights Reserved. Printed in USA.

For more details please go to : www.mar-bal.com/products/standoff-insulators/glastic/

Röchling Glastic Composites

4321 Glenridge Road
44121 Cleveland | OH | USA
www.roechling-industrial.com/glastic

T +1 216 486-0100
F +1 216 486-1091
info@glastic.com

Engineered Composite Materials and Shapes
Durostone® | Glatherm® | Glastic®

